COPENHAGEN
Product Information & Data Sheet

Copenhagen is a predominantly grey natural thin stone veneer. It showcases the beauty that can be achieved when raw stone undergoes multiple processes in our facility. Copenhagen stone is dimensional cut (sawed height) and gets a tumbled finish in our cut shop. The natural limestone slabs are sawed into strips at specified heights (2.25″, 5″, and 7.75″) by a large computer-guided overhead saw. The strips are split with a hydraulic press and the newly formed blocks are fed into the large drum tumbler. Finally, the tumbled blocks are sawn into thin veneer to create Copenhagen.

LEED® Certification & Energy Efficiency

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:

URL
https://quarrymill.com/support

We have resources to help with everything from mortar joint selection to a full PDF install guide.

Flats Dimensions

Heights: 2-¼″, 5″, 7-¾″
Lengths: 4″ – 16″
Depths: ¾″ – 1-½″
Weight: 13 – 15 lb. per square foot

Corner Dimensions

Heights: 2-¼″, 5″, 7-¾″
Lengths: 3″-5″ x 8″-12″
Depths: ¾″ – 1-½″
Weight: 20 lb. per linear foot
Angle: 90

Stone Characteristics

Colors: Grey Tones
Style: Dimensional
Finish: Tumbled

Packaging

Sold as loose pieces.
Flat Pallet: 150 square feet
Corner Pallet: 50 linear feet

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.

🌐 **https://quarrymill.com/shop/copenhagen/**