

CHIEF LEDGE

Product Information & Data Sheet

Chief Ledge is a rough ashlar-style natural thin stone veneer with a pleasing blend of colors. This product consists of a mix of stones from two neighboring mountains. Although still considered quarrying, this stone is extracted from the side of a mountain as opposed to being dug from a quarry pit as is typical of most of our natural stone veneer products. One mountain produces the more natural grey tones, whereas, the other gives the browns, golds, and rust colors. These stark color variations between the two mountain sites are due to the mineral compositions. Large pieces of raw stone are collected and crated up in the mountains and then transported down to our central facility to be processed into natural thin veneer.

Note: This product is currently on backorder. Please contact us before placing an order.

Flats Dimensions

Heights: 2" - 8"
Lengths: 4" - 18"
Depths: ¾" - 1½"
Weight: 13 - 15 lb. per square foot

Corner Dimensions

Heights: 2" - 8"
Lengths: 3"-5" x 8"-12"
Depths: ¾" - 1-½"
Weight: 20 lb. per linear foot
Angle: 90

Stone Characteristics

Colors: Gold Tones, Grey Tones
Style: Ashlar
Finish: Natural

Packaging

Sold as loose pieces.
Flat Pallet: 150 square feet
Corner Pallet: 50 linear feet

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.

<https://quarrymill.com/shop/chief-ledge/>

Natural stone varies in color, shape and veining from piece to piece. Photos used are meant to be as accurate as possible in depicting the product. Photos of stone are meant to give a general idea but should not be used for exact color matching.



LEED® Certification & Energy Efficiency

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:

URL

<https://quarrymill.com/support>

We have resources to help with everything from mortar joint selection to a full PDF install guide.