COBBLE CREEK

Product Information & Data Sheet



Cobble Creek natural thin stone veneer has multiple colors within the individual pieces of stone which creates a unique depth of color. The round pieces or little boulders as they are sometimes called are each unique in size and shape allowing the mason to add their touch of art to the wall. Cobblestones are most commonly found on coastal or lakefront homes. Cobble Creek is not a quarried stone but is collected from natural glacial deposits. Cobblestones can be used for both interior and exterior applications and are well suited for both large and small projects. For masons who are comfortable with and have experience installing cobblestones, they typically go quickly and have a medium to low installation cost.

Flats Dimensions

Heights: 4" - 12" Lengths: 4" - 16"

Depths: 3/4" - 1-1/2"

Weight: 13 - 15 lb. per square foot Weight: 20 lb. per linear foot

Corner Dimensions

Heights: 2" - 8"

Lengths: 3"-5" x 6"-10" Depths: 3/4" - 1-1/2"

Angle: 90

Stone Characteristics

Colors: Earthy Browns, Gold

Tones, Grey Tones Style: Cobblestone

Finish: Natural

Packaging

Sold as loose pieces.

Flat Pallet: 150 square feet Corner Pallet: 50 linear feet

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.



LEED® Certification & **Energy Efficiency**

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:



https://quarrymill.com/info/technical-r esources/

We have resources to help with everything from mortar joint selection to a full PDF install guide.



Nttps://quarrymill.com/shop/cobble-creek/