CAMBRIAN CREEK

Product Information & Data Sheet



Cambrian Creek is a classic real stone veneer cut into the dimensional (sawn-height) style. The stone is natural dolomitic limestone with the timeless colors of gold, buff and the occasional grey. The quarrying and production process for Cambrian Creek is quite impressive. The stone is cut from the ground in blocks roughly the size of a car. Then, the blocks get sawn or sliced as it is called into large sheets of stone in heights of 2.25", 5" and 7.75". The sheets are fed into the splitter where the hydraulic press breaks them every four inches. At this stage, the stone is considered building stone or full veneer. Finally, the pieces are run through the saw to create the beautiful thin veneer.

Flats Dimensions

Heights: 2-1/4", 5", 7-3/4" Lengths: 4" - 16" Depths: 3/4" - 1-1/2"

Weight: 13 - 15 lb. per square foot Weight: 20 lb. per linear foot

Corner Dimensions

Heights: 2-1/4", 5", 7-3/4" Lengths: 3"-5" x 8"-12" Depths: 3/4" - 1-1/2"

Angle: 90

Stone Characteristics

Colors: Gold Tones Style: Dimensional Finish: Natural

Packaging

Sold as loose pieces. Flat Pallet: 150 square feet Corner Pallet: 50 linear feet

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.



LEED® Certification & **Energy Efficiency**

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:



https://quarrymill.com/info/technical-r esources/

We have resources to help with everything from mortar joint selection to a full PDF install guide.



Nttps://quarrymill.com/shop/cambrian-creek/