

LARAMIE

Product Information & Data Sheet

Laramie is an ashlar style split face stone with great natural veining. The veneer is 100% split face and only shows the interior part of the natural stone. The stone has some beautiful swirls and subtle color variation. To create Laramie the slabs of natural stone are peeled out of the quarry. Loaders push their forks between the layers to pop the top layer free. This process is referred to as shelf rock mining. The slabs are between 2"-8" thick and up to eight feet in diameter. Each slab is fed into the hydraulic press one by one where they are split into strips about 4" thick. The strips of split stone are fed into the saw to be cut to a thickness of approximately 1".

Flats Dimensions

Heights: 2" - 8"
Lengths: 4" - 18"
Depths: ¾" - 1½"
Weight: 13 - 15 lb. per square foot

Corner Dimensions

Heights: 2" - 8"
Lengths: 3"-5" x 8"-12"
Depths: ¾" - 1-½"
Weight: 20 lb. per linear foot
Angle: 90

Stone Characteristics

Colors: Copper Tones, Earthy Browns, Gold Tones
Style: Ashlar
Finish: Natural

Packaging

Sold as loose pieces.
Flat Pallet: 150 square feet
Corner Pallet: 50 linear feet

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.

 <https://quarrymill.com/shop/laramie/>

Natural stone varies in color, shape and veining from piece to piece. Photos used are meant to be as accurate as possible in depicting the product. Photos of stone are meant to give a general idea but should not be used for exact color matching.



LEED® Certification & Energy Efficiency

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:

URL

<https://quarrymill.com/support>

We have resources to help with everything from mortar joint selection to a full PDF install guide.