

PENNINGTON

Product Information & Data Sheet

Pennington is a natural Wisconsin quarried dolomitic limestone. The stone is adored for its warm and bright colors including tans and soft reds. The thin veneer process starts with the slabs or sheets of limestone being split into smaller manageable pieces. The slabs are split with a large heavy-duty hydraulic press producing 300 tons of pressure. The pieces are then fed into the diamond blade saw where the thin veneer is cut. Pennington is unique in that the thin veneer is cut exclusively from the edges of the natural stone slabs. This stone is referred to as weathered edge, seamface, or simply rustic due to the unique stratifications in the stone.

Flats Dimensions

Heights: 2" - 8"
Lengths: 4" - 18"
Depths: ¾" - 1½"
Weight: 13 - 15 lb. per square foot

Stone Characteristics

Colors: Copper Tones, Gold Tones
Style: Ashlar
Finish: Natural

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.

 <https://quarrymill.com/shop/pennington/>

Natural stone varies in color, shape and veining from piece to piece. Photos used are meant to be as accurate as possible in depicting the product. Photos of stone are meant to give a general idea but should not be used for exact color matching.



LEED® Certification & Energy Efficiency

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:

URL

<https://quarrymill.com/support>

We have resources to help with everything from mortar joint selection to a full PDF install guide.