PENNINGTON

Product Information & Data Sheet



Pennington is a natural Wisconsin guarried dolomitic limestone. The stone is adored for its warm and bright colors including tans and soft reds. The thin veneer process starts with the slabs or sheets of limestone being split into smaller manageable pieces. The slabs are split with a large heavy-duty hydraulic press producing 300 tons of pressure. The pieces are then fed into the diamond blade saw where the thin veneer is cut. Pennington is unique in that the thin veneer is cut exclusively from the edges of the natural stone slabs. This stone is referred to as weathered edge, seamface, or simply rustic due to the unique stratifications in the stone.

Flats Dimensions

Heights: 2" - 8" Lengths: 4" - 18"

Depths: 3/4" - 11/2"

Weight: 13 - 15 lb. per square foot Weight: 20 lb. per linear foot

Corner Dimensions

Heights: 2" - 8"

Lengths: 3"-5" x 8"-12" Depths: 3/4" - 1-1/2"

Angle: 90

Stone Characteristics

Colors: Copper Tones, Gold

Tones

Style: Ashlar Finish: Natural

Packaging

Sold as loose pieces.

Flat Pallet: 150 square feet Corner Pallet: 50 linear feet

Applications

This natural stone veneer is approved for all applications due to its high compressive strength and low water absorption. It is well suited for exterior applications with a harsh climate.



LEED® Certification & **Energy Efficiency**

Using natural stone veneer can contribute to obtaining credits toward your LEED green building certification. The natural material helps improve the energy efficiency of your home or business.

Installation

Natural thin stone veneer installation information is available on our website:



https://quarrymill.com/info/technical-r esources/

We have resources to help with everything from mortar joint selection to a full PDF install guide.



(https://quarrymill.com/shop/pennington/